

## Industrial / Adhesive Transfer Tape

### 1210A-TT - Permanent Unsupported – Acrylic Adhesive

#### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Bonding &amp; Laminating</li><li>• Mounting foil, metal and plastic name plates</li><li>• Decorative trim</li><li>• Mounting metal and plastic fixtures</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• High peel strength</li><li>• Excellent shear and holding power</li><li>• Bonds to a variety of substrates</li><li>• Excellent temperature resistance</li><li>• Die cuts cleanly</li></ul>
<b>Backing</b>	None
<b>Adhesive</b>	Acrylic
<b>Release Liner</b>	3.5 Mil White Paper – 74# densified kraft
<b>Adhesive Thickness</b>	2 Mil.
<b>Adhesion</b>	60 oz. in/width
<b>Standard Sizes</b>	54" x 250, 500, 750 yards
<b>Temperature Range</b>	-40° F to +250° F
<b>Storage / Shelf Life</b>	One year when stored at 70°F (21°C) 50% RH out of direct sunlight

#### Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship