

## Construction / Seaming Tape

# 2771-9 UV Resistant Polyethylene Tape

## Specifications

<b>Application</b>	<ul style="list-style-type: none"><li>• Splicing and holding polyethylene sheeting.</li><li>• Moving tape.</li><li>• Patching and repairing a variety of surfaces.</li><li>• Indoor and outdoor application.</li><li>• Holding windshield molding in place when replacing it.</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Thick and strong film that conforms well to a variety of surfaces.</li><li>• Aggressive adhesive providing a very high holding power even to irregular surfaces.</li><li>• Water and moisture resistant.</li><li>• Polyethylene film treated to resist UV.</li></ul>
<b>Backing</b>	Polyethylene film
<b>Adhesive</b>	Synthetic rubber
<b>Total Thickness</b>	0.23 mm • 9.0 mil
<b>Adhesion</b>	76 N/100 mm • 75 oz/in
<b>Tensile Strength</b>	438 N/100 mm • 25 lb/in
<b>Elongation</b>	110%
<b>Application Temperature</b>	5 °C - 50 °C • 41 °F - 122 °F
<b>Temperature Resistance</b>	80 °C • 176 °F for 30 minutes
<b>Color</b>	Blue, Clear, White

**N.B. Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.**