

## Industrial Tape / Construction

### 3335B – Black Butyl Rubber Sealant

#### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Metal roof sealing</li><li>• Basement, RV, modular home waterproofing</li><li>• Refrigeration sealant</li><li>• Window glazing</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Withstands extreme roof temperatures</li><li>• Excellent flexibility</li><li>• Superior adhesive strength</li><li>• Resistant to UV light</li><li>• Wide service temperature range</li><li>• Seal not effected by normal movement of building</li></ul>
<b>Adhesive</b>	Butyl Rubber – 100% solids
<b>Liner</b>	3.2 Mil. white silicone paper
<b>Total Thickness</b>	35 Mil. – 1/32"
<b>Service Temp</b>	-60°F to 275°F
<b>Tensile Strength</b>	25 pounds per lineal inch
<b>Water Resistance</b>	Excellent
<b>Application Temperature</b>	40°F to 110°F
<b>Color</b>	Black
<b>Sizes</b>	½", ¾", 1" x 50' / Available in custom sizes
<b>Shelf Life</b>	24 Months

**Note:**

The above value represents average laboratory results. Each user should evaluate the tape to determine the suitability for each and every application and shall assume all risks and liability connection therewith