

Industrial / Adhesive Transfer Tape

4110-TT - Permanent Unsupported – Printed Paper Liner

Specifications:

Application	<ul style="list-style-type: none">• Envelope Closure• Kraft Mailers• Fold over tabs• General purpose bonding
Benefits	<ul style="list-style-type: none">• High peel strength• Excellent shear and holding power• Easy peel extended liner• Wide range service temperature
Backing	None
Adhesive	Permanent Rubber – 1.2 Mil.
Release Liner	Printed Paper – 2.5 Mil. “Remove Liner To Expose Adhesive” Red Print
Total Thickness	3.8 Mil.
Adhesion	100 oz. in/width
Standard Sizes	½” ¾”, 1”, 1.25”, 1.5” x 3000’ (custom sizes available)
Maximum Temperature	93°C • 200 °F
Important	Adhesives Are Compliant With FDA Regulations For Indirect Food Contact – CFR 175.105

Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship