

# Industrial / Adhesive Transfer Tape

## 4125-TT - Permanent Unsupported Printed Paper Liner

### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Tyvek Envelopes &amp; Wrist Bands</li><li>• Permanent envelope closure</li><li>• Tag &amp; label mounting</li><li>• High performance mounting</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• High peel strength</li><li>• Moderate shear and holding power</li><li>• Easy peel extended liner</li><li>• Available Printed instructional liner</li></ul>
<b>Backing</b>	None
<b>Adhesive</b>	Permanent Rubber – 2.5 Mil.
<b>Release Liner</b>	Non Printed Paper – 2.5 Mil. (42# C2S) Available Printed “Remove Liner To Expose Adhesive”
<b>Total Thickness</b>	5 Mil. (Inclusive of Liner)
<b>Adhesion</b>	145 oz. in/width
<b>Maximum Temperature</b>	93°C • 200 °F
<b>Important</b>	Low Slip or No Slip Films are Highly recommended Corona Treatment on Film Surfaces Improves Adhesion Properties Adhesives Are Compliant With FDA Regulations For Indirect Food Contact – CFR 175.105

**Note:**

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or

representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.