

Industrial / Box Sealing Tape

420A BOPP Carton Sealing Acrylic

Specifications

Application

- Holding and bundling application where moisture resistance is required.
- Packaging applications where moisture resistance is required.
- Single strip closure of regular slotted containers (RSC's) dispensed by hand-held case sealer.

Benefits

- Strength.
- High tack.
- Resistance to moisture, chemicals, cold, heat and weathering.
- Impact resistant.
- Water resistant.
- UV resistant.

Backing	Polypropylene film
Adhesive	Water based acrylic adhesive
Total Thickness	2.1 mil
Adhesion	26 oz/in
Tensile Strength	23 lb/in
Application Temperature	7 °C • 45 °F
Temperature Resistance	-22 °F to 130 °F
Color	Clear

Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.