

## Industrial / Double-Sided Tape

### 4409W Double-Sided UPVC Tape

## Specifications

- Application**
- General mounting: nameplates and trophies, vinyl extrusions, metal fittings, vertical blinds, automotive trim, display boxes.
  - Rubber and plastic trim for weather stripping, decorative trim, furniture trim, appliance trim and nameplates.

- Benefits**
- Excellent resistance to UV and aging.
  - Good shear resistance at normal and elevated temperature.
  - Good tack, high adhesive mass.
  - Acrylic adhesive system.

<b>Backing</b>	White UPVC
<b>Tensile Strength</b>	Solvent based acrylic
<b>Liner</b>	Silicone paper – mustard Color
<b>Total Thickness</b>	8.0 mil
<b>Adhesion</b>	130 oz./inch - 37 N/25mm
<b>Shear Strength</b>	60 N/625mm
<b>Temperature Range</b>	-40 °C to 80°C
<b>Color</b>	White

**Note:**

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship