

## Industrial / Double-Sided Tape

## 4412-TDE Reinforced Tissue Tape – Permanent Rubber Adhesive

## Specifications:

Application	<ul> <li>General purpose bonding of film, paper and fabrics</li> <li>Point of purchase displays</li> <li>Seaming low profile materials</li> <li>Core starting</li> </ul>
Benefits	<ul> <li>High tack, high shear adhesive</li> <li>Low profile</li> <li>Easy removal true dry edge</li> </ul>
Backing	Micro-Tissue
Adhesive Type	Synthetic Rubber
Liner	42# Printed Black Silicone Paper Liner
	Black Ink "Remove Liner To Expose Adhesive"
Total Thickness	5 Mil.
Adhesion	100 oz./in width
Maximum Temperature	55°C • 130 °F
Color	Off-White
Available Sizes	½", ¾", 1" x 216', 1300', 2500 and 3,000'

## Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.