

## Industrial / Transfer Tape

### 4459-ATG – High Performance Acrylic

#### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• General industrial assembly</li><li>• Point-of-purchase</li><li>• Commercial Printing</li><li>• Graphic arts applications</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Versatile and convenient</li><li>• Quick use binding &amp; affixing</li><li>• Excellent holding power at elevated temperatures</li><li>• Shorts runs avoids set up</li></ul>
<b>Backing</b>	None
<b>Adhesive</b>	Acrylic
<b>Liner</b>	3.2 mil – Brown
<b>Total Thickness</b>	5 Mils.
<b>Adhesion to Steel</b>	75 oz/in
<b>Available Sizes</b>	½" x 18 yds - ½" x 36 yds / ¾" x 18 yds – ¾" x 36 yds
<b>Tack</b>	1 /in
<b>Operating Temperature</b>	10°F to 180 °F 10°F to 180 °F 10°F to 275°F (short term)
<b>Color</b>	Clear

#### Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship.