

## Industrial / Double-Faced Tape

# 4472 – Double-Faced Film Supported Tape 53# Paper Liner

## Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Polybag Bag Closure</li><li>• Splicing Low Energy Plastics</li><li>• Laminating Non-Woven Fabrics</li><li>• Affixing Dissimilar Substrates</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Excellent quick Stick</li><li>• Good Shear and Holding Strength</li><li>• Easy Release Paper Liner</li><li>• Available Instructional Printed Liner</li></ul>
<b>Backing</b>	1.2 Mil Clear BOPP
<b>Adhesive</b>	Exposed: 3 mil. Permanent Rubber Liner Side: 3 mil. Permanent Rubber
<b>Release Liner</b>	3.2 mil. (54#) Densified Kraft Paper Type
<b>Total Thickness</b>	7.2 millimeters (exclusive of liner)
<b>Adhesion</b>	180 oz. in/width
<b>Tensile Strength</b>	22 lbs. in /width
<b>Elongation</b>	75 % at break
<b>Holding Power</b>	10,000+ minutes
<b>Max Temperature</b>	180 °F • 82 °C
<b>Important</b>	Adhesives Are Compliant With FDA Regulations For Indirect Food Contact – CFR 175.105

### Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship