

## Construction / Seaming Tape

### 4805-W Contractors Sheathing Tape

#### Specifications:

- Application**
- Overlaps splicing of insulation materials.
- Benefits**
- Excellent adhesion to insulation materials.
  - Good low temperature performance.
  - Good U.V. stability.
  - Good High temperature performance.

<b>Backing</b>	U.V. Treated polypropylene film
<b>Adhesive</b>	Solvent Based acrylic
<b>Total Thickness</b>	3.0 mil
<b>Adhesion</b>	45 oz/in
<b>Tensile Strength</b>	29 lb/in
<b>Application Temperature</b>	14 °F to 122 °F
<b>Temperature Resistance</b>	212 °F
<b>Color</b>	White
<b>Meets CDN Spec.</b>	CCMC #11955
<b>VOC (Volatile Organic Compound) content</b>	Estimated 0,1%
<b>Moisture Vapor Transmission Rate</b>	3.9x10 <sup>-9</sup> g/Pa s m <sup>2</sup>
<b>Water Penetration Rate</b>	0.009 g/100 in <sup>2</sup>

**Note:**

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.