

Adhesives · Machinery · Tape

Industrial / Double-Sided Tape

5120 - Double-Sided Polyester

Specifications:

Application • Mounting point of purchase displays

Mounting shelving materialsHolding posters and retail signs

· Loyalty price change tag backing

• Clean removability from Paint, metal, glass, and

aluminum

• Excellent cold temperature performance

True dry edge easy removal liner

Extra long length rolls

Carrier 0.5 mil. Polyester

Liner Adhesive 1 mil. Synthetic RubberUnwind Adhesive 1.3 mil. Synthetic RubberLiner 3.2 mil. White Silicone Paper

Total Thickness 5.8 mil.

Adhesion SS Exposed Side: 150 oz/in

Liner Side: 100 oz/in

Loop Tack SS 80 oz.

Color Light Amber

Standard Sizes ½" ¾" 7/8" 1" x 2500'/3,000'/3500'/4500'

Surface Preparation Surface tape is applied must be clean, dry and free of

grease or oil.

Note:

All statements, techincal information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not costitute a gaurentee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship.