

## Industrial / Double-Sided Tape

### 5610-TDE Double-Sided Polyester Differential Permanent / Removable

#### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Temporary holding</li><li>• Resealable Bag closure</li><li>• Holding posters and signage</li><li>• Core Starting</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Repositionable (Low tack side)</li><li>• Removes cleanly (Low tack side)</li><li>• Easy to handle</li><li>• High tack / high shear</li></ul>
<b>Backing</b>	0.50 mil. Clear Polyester
<b>Adhesive</b>	Synthetic rubber
<b>Liner</b>	White silicone paper Available "To Expose Adhesive Remove Liner"
<b>Total Thickness</b>	3.0 mil.
<b>Adhesion</b>	Exposed Side: 80 oz/in Liner Side: 10 oz./in
<b>Elongation</b>	10 %
<b>Sizes</b>	½", 5/8", ¾", 1" x 3,000' – Spools Available 30" and 59" Masters
<b>Available Versions</b>	Printed Liner – True Dry Edge – Lift Edge
<b>Maximum Temperature</b>	55°C • 130 °F

**Note:** All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.