

Industrial / Double-Sided Tape

5615A-TDE Double-Sided Polyester Permanent / Removable

Specifications:

Application	<ul style="list-style-type: none">• Temporary holding• Resealable Bag closure• Holding posters and signage• Core Starting
Benefits	<ul style="list-style-type: none">• Repositionable (Low tack side)• Removes cleanly (Low tack side)• Extended liner for easy removal• Easy to handle• Low tack / high shear
Backing	0.50 mil. Clear Polyester
Adhesive	Closed Side: Acrylic Exposed Side: Rubber
Liner	42# Silicone paper (2.5 mil.) Available "To Expose Adhesive Remove Liner"
Total Thickness	3.5 mil.
Adhesion	Exposed Side: Permanent Liner Side: Removable
Elongation	10 %
Available Sizes	½", ¾", 1" x 3000' / Spools up to 21,000'
Available Versions	Printed Liner – True Dry Edge – Lift Edge
Maximum Temperature	55°C • 130 °F

Note: All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.