

## Industrial / Double-Sided Tape

## 6700RT-TDE Double-Sided Polyester Permanent Bag Closure / Red Print

## Specifications:

Application Benefits	<ul> <li>Permanent bag closure</li> <li>Permanent seaming tape</li> <li>Protective pouch closure</li> <li>Document pouch closure</li> <li>Immediate bond when sealed</li> <li>Easy peel true dry edge</li> <li>Hot knife cuttable</li> </ul>
Backing Adhesive Release Liner Total Thickness Adhesion Size Maximum Temperature	Polyester5 Mil. Clear Permanent Rubber Clear PET – 1.4 Mil. "Red Tint" 4.1 Mil. 100 oz. in/width ½", ¾", 1" x 3,000' / 21,000' spool 55°C • 155 °F
Important	Low Slip or No Slip Films are Highly recommended Corona Treatment on Film Surfaces Improves Adhesion Properties

## Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.