

Adhesives · Machinery · Tape

Industrial / Double-Sided Tape

6700 - Double-Sided Polyester Permanent Bag Closure / White Poly Liner

Specifications:

Application • Permanent Bag closure

Permanent seaming tapeProtective pouch closureDocument pouch closure

Benefits • Immediate bond when sealed

• Easy Peal True Dry Edge

Hot Knife Cuttable

BackingPolyester - .5 Mil. ClearAdhesivePermanent RubberRelease LinerWhite BOPP - 1.8 Mil.

Total Thickness 4.1 Mil.

Adhesion 100 oz. in/width

Size ½", ¾", 1" x 3,000' / 21,000' spool

Maximum 55°C • 155 °F Temperature

Important Low Slip or No Slip Films are Highly recommended

Corona Treatment on Film Surfaces Improves Adhesion

Properties

Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.