

## Industrial / Double-Faced Tape

# 7750R- Red Tissue Supported – Acrylic Adhesive

## Specifications:

- Application**
- Bonding & laminating
  - Bonding low Energy Plastics
  - Locate splices @ high speed
  - Mounting metal and plastic fixtures

- Benefits**
- High peel strength
  - Hand Tear-able
  - Excellent shear and holding power
  - Bonds to a variety of substrates
  - Excellent temperature resistance
  - Plasticizer resistant

<b>Backing</b>	Micro-Tissue
<b>Adhesive</b>	Rubber Based
<b>Release Liner</b>	3.5 Mil. White Paper – 60# densified kraft
<b>Total Thickness</b>	5.5 Mil.
<b>Adhesion</b>	90 oz. in/width
<b>Standard Sizes</b>	54" x 250, 500, 750 yards
<b>Temperature Range</b>	-0° F to + 250° F Short Term – 180°F Long Term
<b>Storage / Shelf Life</b>	One year when stored at 70°F (21°C) 50% RH out of direct sunlight

**Note:**

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship