

## Industrial / Box Sealing Tape

# 819C Clear BOPP Carton Sealing Tape

## Specifications:

- Application**
- Aggressive instant sealing to medium weight boxes
  - Resistant to aging, weathering, UV light and yellowing
  - Superior quick-stick performance , and controlled unwind to facilitate dispensing

**Backing** Biaxially Oriented Polypropylene

**Adhesive** Synthetic Rubber

**Total Thickness** 1.9 mil.

	<b>Value</b>	<b>Test Method</b>
<b>Adhesion</b>	42 oz/in	ASTM D-3330
<b>Elongation</b>	120% TD	ASTM D-882
<b>Tensile Strength</b>	24 lbs/in width	ASTM D-3759
<b>Unwind Adhesion</b>	13 oz/in 30 min conditioning	ASTM D-3330/D330M-04
<b>Application Temperature</b>	32°F to 120 °F	
<b>Storage &amp; Handling</b>	Two years when stored at 70°F and 50% relative humidity Avoid temperature and humidity extremes.	
<b>Color</b>	Clear	

### Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.